
AXTAL ADVANCED XTAL PRODUCTS

Specification	AXQW76-0.5-38-SSP	Rev.: 1	Date: 2014-06-24
Oscillator type :	Quartz Wafer 3” Diameter (38°) for SAW Application		

Parameter	min.	typ.	max.	Unit	Condition
Wafer diameter	76.1	76.2	76.3	mm	
Cut angle Theta		38° ± 5’			
Thickness	0.48	0.50	0.52	mm	
Reference flat	21	23	25	mm	
Orientation		-X axis			
Cut Identification		3 slots			On reference flat
Bevel		0.3 x 0.075		mm	On polished side, see drawing
Surface finish					
Front side: polished with Ra			0.5	nm	AFM
Back side: fine lapped with Ra	0.2		0.5	µm	GC#2000
Flatness:					
Bow			40	µm	
LTV		3	5	µm	
TTV		5	7	µm	
Warp		40	50	µm	
Seed			5	mm	Centred along X-axis, see drawing. No holes
Quality		SAW grade			Note 1
Quartz material		Q> 1.8 million ID Grade II, RH ECD < 100 cm^{-2}			
Edge chips			0.5	mm	In radial direction, Note 2
Packing		Plastic bags			Note 3

Notes:

1. Terminology and test conditions are according to IEC standard IEC 60758 and IEC 62276
2. No chips in work area (2 mm from circumference)
3. Packing in shipper or wafer box on request



AXTAL GmbH & Co. KG
Roemering 9
D-74821 Mosbach
Germany

www.AXTAL.com
fon: +49 (6261) 939834
fax: +49 (6261) 939836
E-mail: info@axtal.com