
AXTAL ADVANCED XTAL PRODUCTS

Specification	AXQCM496-Ag	Rev.:3	Date: 2014-06-02


Type : Quartz Crystal Microbalance Element (Monitor Crystal)

Parameter	min.	typ.	max.	Unit	Condition
Nominal frequency		5.000		MHz	
Adjustment frequency		4.960		MHz	
Crystal cut		AT			
Overtone		1			
Adjustment tolerance	-7		+7	kHz	@ 25°C
Frequency stability					
Over operating temperature range	0		+70	ppm	
Resonance resistance R_r			15	Ω	
Motional capacitance C_1				fF	
Shunt capacitance C_0			7	pF	
Drive level		100		µW	
Operating temperature range	0		+70	°C	
Storage temperature range	-40		+105	°C	
QCM diameter		13.97+0-0.03		mm	
Blank surface quality		Fine lapped			
Electrode diameter Side A		13.3 ± 0.1		mm	Fully plated
Electrode material Side A		Cr-Ag			
Electrode diameter Side B		6.0		mm	See drawing
Electrode material Side B		Cr-Ag			

Side A (Plane)



Side B (Convex)



Ordering Code:

Model (Specification)	Frequency [MHz]
AXQCM496-Ag	4.960

AXTAL GmbH & Co. KG
Roemerring 9
D-74821 Mosbach
Germany

www.axtal.com
fon: +49 (6261) 939834
fax: +49 (6261) 939836
E-mail: info@axtal.com

Revision History

Rev.	Drawing	Date [dd.mm.yyyy]	Remarks	Author	Checked
3	D0	16.10.2013		EP	BN
3	D1	02.06.2014	Editorial changes	BN	BN